

Chalkspray - 1013100 to 1013106

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : Chalkspray  
Product code : 1013100 to 1013106.  
UFI : H200-U0CW-500E-QK7F

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : Allbuyone GmbH.  
Address : Obere Bahnhofstrasse 58.D-82110.Germering.Allemagne.  
Telephone : +49 89-1 22 89 06 10 . Fax : .  
www.allbuyone.com

#### 1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

#### Other emergency numbers

INTERNATIONAL SUPPORT : <http://echa.europa.eu/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks>

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).  
Repeated exposure may cause skin dryness or cracking (EUH066).  
Eye irritation, Category 2 (Eye Irrit. 2, H319).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).  
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.  
The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

#### 2.2. Label elements

Mixture for aerosol application.

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

607-022-00-5 ETHYL ACETATE

Additional labeling :

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P102

Keep out of reach of children.

**Chalkspray - 1013100 to 1013106**

Precautionary statements - Prevention :

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.

Precautionary statements - Storage :

- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Other information :

- Do not use in a confined space.  
Not to be used for any usage other than those specified.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE	GHS02, GHS04 Dgr Flam. Gas 1, H220	C [1] [7]	10 $\leq$ x % < 25
CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21  PROPANE	GHS02 Dgr Flam. Gas 1, H220	[1] [7]	10 $\leq$ x % < 25
INDEX: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46  ETHYL ACETATE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	10 $\leq$ x % < 25
EC: 919-857-5 REACH: 01-2119463258-33  DEAROMATIZED HYDROCARBONS	GHS08, GHS07, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH:066	P	10 $\leq$ x % < 25
CAS: 75-28-5 EC: 200-857-2 REACH: 01-2119485395-27  ISOBUTANE (CONTENANT MOINS DE 0.1% DE BUTADIENE)	GHS02 Dgr Flam. Gas 1, H220	[1] [7]	10 $\leq$ x % < 25
INDEX: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5  TITANIUM DIOXIDE [IN POWDER FORM CONTAINING 1 % OR MORE OF PARTICLES WITH AERODYNAMIC DIAMETER $\leq 10 \mu\text{M}$ ]	GHS08 Wng Carc. 2, H351	[1] [10]	2.5 $\leq$ x % < 10
CAS: 8042-47-5 EC: 232-455-8 REACH: 01-2119487078-27  HUILE MINERALE BLANCHE	GHS08 Dgr Asp. Tox. 1, H304	[1]	2.5 $\leq$ x % < 10

**Chalkspray - 1013100 to 1013106**

**Specific concentration limits:**

Identification	Specific concentration limits	ATE
CAS: 8042-47-5 EC: 232-455-8 REACH: 01-2119487078-27 HUILE MINERALE BLANCHE		inhalation: ATE = 5 mg/l (vapours)

**Information on ingredients :**

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[7] Propellant gas

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures**

**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder

**Chalkspray - 1013100 to 1013106**

- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water
- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

**Chalkspray - 1013100 to 1013106**

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
141-78-6	734	200	1468	400	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
74-98-6	1000 ppm				
141-78-6	400 ppm				
75-28-5	1000 ppm				
13463-67-7	10 mg/m3			A4	

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m3	750 ppm 1810 mg/m3		Carc	
141-78-6	200 ppm 734 mg/m3	400 ppm 1468 mg/m3			
13463-67-7	4 mg/m3				

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
141-78-6	200	734	400	1468	-	84
13463-67-7	-	10	-	-	-	-

- Netherlands / MAC-waarde (10 december 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm	-	-	-	-
141-78-6	150 ppm	300 ppm	-	-	-
13463-67-7	10 mg/m3	-	-	-	-

**Chalkspray - 1013100 to 1013106****- Denmark (2020) :**

Stof	TWA	VSTEL	Loftvaerdi	Anm
106-97-8	500 ppm 1200 mg/m <sup>3</sup>			
74-98-6	1000 ppm 1800 mg/m <sup>3</sup>			
141-78-6	150 ppm 540 mg/m <sup>3</sup>			E
13463-67-7	6 mg/m <sup>3</sup>			K

**- Norway (Veiledning om administrative normer for forurensning i arbeidsatmosfære, 2019) :**

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	250 ppm 600 mg/m <sup>3</sup>				
74-98-6	500 ppm 900 mg/m <sup>3</sup>				
141-78-6	200 ppm 734 mg/m <sup>3</sup>	400 ppm 1468 mg/m <sup>3</sup>		E	
13463-67-7	5 mg/m <sup>3</sup>				

**- Switzerland (Suva 2021) :**

CAS	VME	VLE	Valeur plafond	Notations
106-97-8	800 ppm 1900 mg/m <sup>3</sup>	3200 ppm 7600 mg/m <sup>3</sup>		
74-98-6	1000 ppm 1800 mg/m <sup>3</sup>	4000 ppm 7200 mg/m <sup>3</sup>		
141-78-6	200 ppm 730 mg/m <sup>3</sup>	400 ppm 1460 mg/m <sup>3</sup>		
75-28-5	800 ppm 1900 mg/m <sup>3</sup>	3200 ppm 7600 mg/m <sup>3</sup>		
13463-67-7	3 ppm			
8042-47-5	5 ppm			

**- Finland (HTP-värden 2018) :**

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
74-98-6	800 ppm 1500 mg/m <sup>3</sup>	1100 ppm 2000 mg/m <sup>3</sup>			
141-78-6	200 ppm 730 mg/m <sup>3</sup>	400 ppm 1470 mg/m <sup>3</sup>			

**- Sweden (AFS 2018 :1) :**

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
141-78-6	150 ppm 550 mg/m <sup>3</sup>	300 ppm 1100 mg/m <sup>3</sup>			
13463-67-7	5 mg/m <sup>3</sup>				

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):****DEAROMATIZED HYDROCARBONS****Final use:**

Exposure method:  
Potential health effects:  
DNEL :

Exposure method:  
Potential health effects:  
DNEL :

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

Exposure method:  
Potential health effects:

**Workers.**

Dermal contact.  
Long term systemic effects.  
300 mg/kg body weight/day

Inhalation.  
Long term systemic effects.  
1500 mg of substance/m<sup>3</sup>

**Consumers.**

Ingestion.  
Long term systemic effects.  
300 mg/kg body weight/day

Dermal contact.  
Long term systemic effects.

**Chalkspray - 1013100 to 1013106**

DNEL : 300 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term systemic effects.  
DNEL : 900 mg of substance/m<sup>3</sup>

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### Physical state

Physical state : Viscous liquid.

#### Colour

Unspecified

#### Odour

Odour threshold : Not stated.

#### Melting point

Melting point/melting range : Not specified.

#### Freezing point

Freezing point / Freezing range : Not stated.

#### Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

#### Flammability

Flammability (solid, gas) : Not stated.

#### Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

#### Flash point

Flash point interval : Not relevant.

#### Auto-ignition temperature

Self-ignition temperature : Not specified.

#### Decomposition temperature

Decomposition point/decomposition range : Not specified.

#### pH

pH : Not relevant.

pH (aqueous solution) : Not stated.

#### Kinematic viscosity

Viscosity : Not stated.

#### Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

#### Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

#### Vapour pressure

Vapour pressure (50°C) : Not relevant.

#### Density and/or relative density

Density : < 1

#### Relative vapour density

Vapour density : Not stated.

### 9.2. Other information

No data available.

#### 9.2.1. Information with regard to physical hazard classes

No data available.

#### Aerosols

Chemical combustion heat : Not specified.

Inflammation time : Not specified.

Deflagration density : Not specified.

Inflammation distance : Not specified.

Flame height : Not specified.

Flame duration : Not specified.

#### 9.2.2. Other safety characteristics



**Chalkspray - 1013100 to 1013106**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat
- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

**10.5. Incompatible materials**

Keep away from :

- water

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

**11.1.1. Substances**

**Acute toxicity :**

HUILE MINERALE BLANCHE (CAS: 8042-47-5)

Inhalation route (Vapours) : LC50 = 5 mg/m<sup>3</sup>

DEAROMATIZED HYDROCARBONS

Oral route : LD50 > 5000 mg/kg  
Species : Rat

Dermal route : LD50 > 5000 mg/kg  
Species : Rabbit

Inhalation route (n/a) : LC50 > 4951 mg/m<sup>3</sup>  
Species : Rat

**11.1.2. Mixture**

No toxicological data available for the mixture.

**11.2. Information on other hazards**

**Chalkspray - 1013100 to 1013106**

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

**DEAROMATIZED HYDROCARBONS**

Fish toxicity :

LC50 > 1000 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 1000 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Algae toxicity :

ECr50 > 1000 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 72 h

Aquatic plant toxicity :

Species : Others

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

**12.2.1. Substances**

**DEAROMATIZED HYDROCARBONS**

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

16 05 04 \* gases in pressure containers (including halons) containing dangerous substances

**Chalkspray - 1013100 to 1013106**

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

**14.1. UN number or ID number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

**- Container information:**

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): <https://echa.europa.eu/substances-restricted-under-reach>.

**- Particular provisions :**

No data available.

**- Swiss ordinance on the incentive tax on volatile organic compounds :**

75-28-5                      2-méthylpropane (alcool isobutylique, isobutane)  
141-78-6                    acétate d'éthyle  
78-93-3                      butanone (méthyléthylcétone)  
74-98-6                      propane  
106-97-8                    n-butane

**Chalkspray - 1013100 to 1013106**

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer .
EUH066	Repeated exposure may cause skin dryness or cracking.

**Abbreviations :**

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.  
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.  
EC50 : The effective concentration of substance that causes 50% of the maximum response.  
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.  
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.  
ATE : Acute Toxicity Estimate  
DNEL : Derived No-Effect Level  
UFI : Unique formulation identifier.  
STEL : Short-term exposure limit  
TWA : Time Weighted Averages  
TMP : French Occupational Illness table  
TLV : Threshold Limit Value (exposure)  
AEV : Average Exposure Value.  
ADR : European agreement concerning the international carriage of dangerous goods by Road.  
IMDG : International Maritime Dangerous Goods.  
IATA : International Air Transport Association.  
ICAO : International Civil Aviation Organisation  
RID : Regulations concerning the International carriage of Dangerous goods by rail.  
WGK : Wassergefährdungsklasse (Water Hazard Class).  
GHS02 : Flame  
GHS07 : Exclamation mark  
PBT: Persistent, bioaccumulable and toxic.  
vPvB : Very persistent, very bioaccumulable.  
SVHC : Substances of very high concern.